

# BARRACUDA

ENGINE	225	318	340	383-2 BBL	383-4 BBL	440-HP & 3-2 BBL	426 HEMI
CAPACITY (With Heater) Quarts—							
Radiator Width .....	13-19" 14-22"	16-19" 17.5-26"	15.5-26"	14.5-22" 15-26"	14.5-22" 15-26"	17-26"	17-26"
RADIATOR—Identification Number—Width							
Transmission Manual 230 .....	2998936-19"	2998946-19"	2998974-26"				
833 .....			2998974-26"	N/A	2998954-22"	2998958-26"	2998956-26"
Automatic 904 .....	2998937-19"	2998947-19"					
727 .....			2998974-26"	2998957-22"	2998960-22"	2998960-26"	2998956-26"
Air Conditioning .....	2998938-22"	2998948-26"	2998974-26"	2998958-26"	2998961-26"	2998961-26"	N/A
Maximum Cooling .....	2998939-22"	2998949-26"	2998949-26"	2998956-26"	2998956-26"	2998956-26"	N/A
Oil Cooler Size—Standard .....	10"	10"	10"	12"	12"	12"	12"
Air Conditioning .....	10"	10"	10"	12"	12"	12"	N/A
Maximum Cooling .....	12"	12"	12"	12"	12"	12"	N/A
Shroud Transmission Manual .....	None	None		N/A	Yes△	Yes	Yes
Automatic .....	None	None		None	Yes△	Yes	Yes
Air Conditioning .....	Yes	Yes	Yes	Yes	Yes	Yes**	N/A
Maximum Cooling .....	Yes	Yes	Yes	Yes	Yes	Yes	N/A
Seal .....							
Hood to Yoke .....	Yes****	Yes	Yes	Yes	Yes	Yes	Yes
FAN							
Diameter—Number Blades—Width							
Standard .....	17-4-1-1/2	18-4-2 B.T.	18-1/2-7-2-1/2		18-7-2	18-1/2-7-2-1/2	18-1/2-7-2-1/2
Automatic .....	17-4-1-1/2	18-4-2 B.T.	18-1/2-7-2-1/2	18-7-2	18-7-2	18-7-2	18-1/2-7-2-1/2
Air Conditioning .....	18-4-2 P.T.	18-1/2-7-2-1/2	18-1/2-7-2-1/2	18-1/2-7-2-1/2	18-1/2-7-2-1/2	18-1/2-7-2-1/2	N/A
High Capacity .....	18-7-1-1/2	18-7-2-1/4	N/A	18-7-2-1/8	18-7-2-1/8	18-7-2-1/8	N/A
Spacer							
Standard .....	1.72"	2.20"	Torque	1.60"	1.60"	Torque—Manual 1.60"—Automatic	Torque
Air Conditioning .....	1.72"	Thermal	Thermal	Thermal	Thermal	Thermal**	N/A
High Capacity .....	1.72"	2.20"	Torque	1.60"	1.60"	1.60"	N/A
Ratio (Fan to Crankshaft)							
Standard .....	1.07:1	.95:1	.95:1	.95:1	.95:1	.95:1	1.20"1
Air Conditioning .....	1.07:1	1.3:1	1.3:1	1.4:1	1.4:1	1.4:1	N/A
High Capacity .....	1.07:1	.95:1	.95:1	.95:1	.95:1	.95:1	N/A
WATER PUMP IMPELLER							
Diameter—Number Blades							
Standard .....	3.50"-6	4.38"-8	4.38"-8	4.38"-8	4.38"-8	4.38"-8	4.38"-8
Air Conditioning .....	3.50"-6	3.70"-6	3.70"-6	3.50"-6	3.50"-6	3.50"-6**	N/A

\* Add one quart with Maximum Cooling.

\*\* Air Conditioning not available on 440 Cubic Inch with 3-2 BBL.

\*\*\* Auxiliary 7" x 26" Oil Cooler (air cooled) in series with standard oil cooler.

\*\*\*\*Air Conditioning and Maximum Cooling only.

△ 383-4BBL with High Performance Camshaft only.